



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: SHIELD PERFORMANCE 4T SAE 20W40	DATE : 06/09/2018
BATCH NO: SL/18-09/482	

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION		BATCH TEST REPORT
				Min	Max	
1	Appearance	Visual	-	Cl & Br	-	Cl & Br
2	Crackle test	Visual			Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/m ³	Report	-	0.8673
4	Colour	ASTM D 1500			Red	Red
5	Kinematic Viscosity @ 100°C	ASTM D 445	mm ² /s	14	15.50	15.08
5	Kinematic Viscosity @ 40°C	ASTM D 445	mm ² /s	Report		130.4
7	Viscosity Index	ASTM D 2270		110	-	118
8	Flash Point (COC)	ASTM D 92	deg.C	220		234
9	Pour Point	ASTM D 97	deg.C	-	-24	-24
10	Total Base Number	ASTM D2896	MgKOH/g	5.50		7.21

Remark: sample pass

Tested By: Sandip Bhayaje

Approved By:

Regd.Office: Shelton Sapphire,8TH Floor,806-B,Plot No:18-19,Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra.India.
L—022-27582828,Website-www.shieldlubricants.com