



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME : SHIELD FLEET POWER MULTI 20W40	DATE : 01/06/2019
BATCH NO : SL/19-05/1468	

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION		BATCH TEST REPORT
				MINIMUM	MAXIMUM	
1	Appearance	Visual	Cl & Br		Cl. & Br.
2	Crackle Test	Visual	Nil		Nil
3	Colour	ASTM D-1500	Red		Red
4	Density @29.5°C	ASTM D-1298	Kg/m ³	Reported		0.8832
5	Kin Visc.@100°C	ASTM D-445	mm ² /s	14.00	15.50	15.41
6	Kin Visc.@40°C	ASTM D-445	mm ² /s	Reported		136.5
7	Viscosity Index	ASTM D-2270	110		116
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	8.00		9.00
9	Flash Point	ASTM D92	°C	220		236
10	Pour Point	ASTM D97	°C		-21	-27

Remark: sample pass

Tested By: Sandip Bhayaje

Approved By:

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com