



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: SHIELD FLEET POWER MAX SAE 15W40 API CF-4	DATE : 03/01/2021
BATCH NO : SL/21-01/1316	LAB.SR.NO-608

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION		BATCH TEST REPORT
				MINIMUM	MAXIMUM	
1	Appearance	Visual	Clear & Bright		Clear & Bright
2	Crackle Test	Visual	Nil		Nil
3	Colour	ASTM D-1500	L4.0 Max.		L2.0
4	Density @29.5°C	ASTM D-1298	Kg/m ³	Reported		0.8676
5	Kinematic Viscosity @ 100°C	ASTM D-445	Cst	14.00	15.50	15.34
6	Kinematic Viscosity @ 40°C	ASTM D-445	Cst	Reported		117.8
7	Viscosity Index	ASTM D-2270	130		136
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.50		10.04
9	Flash Point ,COC	ASTM D-92	°C	220		230
10	Pour Point	ASTM D-97	°C		-24	-27

Remark: sample pass

Tested By: Anil Jarhad

Approved By: Sandip Bhayaje

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com