



LABORATORY TEST REPORT

PRODUCT NAME : SHIELD FLEET POWER TURBO 15W40 API CH-4	DATE :20/07/2021
BATCH NO : SL/21-07/391	SR NO- 267

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/L	Reported	0.8641
5	Kinematic Viscosity @ 100°C	ASTM D-445	cST	14.00 Min. - 15.50 Max.	15.38
6	Kinematic Viscosity @ 40°C	ASTM D-445	cST	Reported	118.5
7	Viscosity Index	ASTM D-2270	135 Min.	136
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	10.00 Min.	10.21
9	Flash Point ,COC	ASTM D-92	°C	220 Min.	224
10	Pour Point	ASTM D-97	°C	-33 Max.	-33

REMARK: SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE