



**LABORATORY TEST REPORT**

PRODUCT NAME:SHIELD HYDRAULIC OIL AW 68 ISO VG 68	DATE : 21/07/2021
BATCH NO : SL/21-07/395	LAB.SR.NO - 271

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle test	Visual	....	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/L	Reported	0.8434
4	Colour	ASTM D 1500	....	L2.5 Max.	L1.5
5	Kinematic Viscosity @ 40°C	ASTM D 445	cST	61.2 Min. - 74.8 Max.	64.94
6	Kinematic Viscosity @ 100°C	ASTM D 445	cST	Reported	10.71
7	Viscosity Index	ASTM D2270	....	90 Min.	155
8	Pour Point	ASTM D97	°c	-3 Min.	-15
9	Flash Point ,COC	ASTM D92	°c	210 Min.	214
10	Foaming, Tendency/Stability.				
	Sequence I at 24±0.5°C	ASTM D892	ml	150/0 Max.	10/0
	Sequence II at 93.5±0.5°C		ml	75/0 Max.	0/0
	Sequence III at 24±0.5°C		ml	150/0 Max.	10/0

**REMARK: SAMPLE PASS**

**TESTED BY: ANIL JARHAD**

**APPROVED BY: SANDIP BHAYAJE**