



Shield Lubricants & Specialities Pvt. Ltd.

CERTIFICATE OF ANALYSIS

PRODUCT NAME : FLEET POWER SYNERGY 20W40 API CH4	DATE : 10/08/2024
BATCH NO. : SL/24-08/766	LAB.SR.NO.: 535

Sr. No.	Tests	Units	Method	Minimum	Maximum	Test Results
1	Appearance	Visual	Clear & Bright		Clear & Bright
2	Crackle Test	Visual	Nil		Nil
3	Density @ 29.5°C	Kg/ml	ASTM D1298	Report		0.8711
4	Colour	ASTM D1500		L4.0	L2.0
5	Kinematic,Viscosity @ 40°C	cSt	ASTM D445	Report		123.7
6	Kinematic,Viscosity @ 100°C	cSt	ASTM D445	14	15.5	14.75
7	Viscosity Index	ASTM D2270	Report		121
8	Total Base Number, TBN	mg KOH/g	ASTM D2896	9.5		9.57
9	Flash Point, COC	°C	ASTM D92	210		232
10	Pour Point	°C	ASTM D97		-24	-24

REMARK: SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.