



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: SHIELD RUSTIC 30	DATE : 25/11/2024
BATCH NO: SL/24-11/1402	LAB.SR.NO. – 956

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8718
3	Colour	ASTM D 1500	L3.0 Max.	L2.5
4	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	Report	33.82
5	Flash Point COC.	ASTM D-92	°C	150 Min.	196
6	Water Displacement Test	Pass
7	Cu Corrosion Test@100°C	ASTM D130	°C	1A PASS	1A pass
8	Salt Spray Test	ASTM B117-2003	Hrs.	20 Min. - 30 Max.	28

REMARK: SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com