



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT.NAME. :SHIELD PERFORMANCE TECH 4T 15W50 API SM	DATE : 26/11/2024
BATCH. NO. : SL/24-11/1410	LAB.SN.NO. – 963

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright.
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8568
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	17.50 Min. - 20.50 Max.	18.75
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	152.3
7	Viscosity Index	ASTM D-2270	130 Min.	139
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.30 Min.	8.20
9	Flash Point , COC	ASTM D-97	°C	200 Min.	232
10	Pour Point	ASTM D-92	°C	-24 Max.	-33

REMARK: SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com