



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME :SHIELD MFL 150 ISO 150	DATE : 14/12/2024
BATCH NO. : SL/24-12/1551	LAB.SR.NO. -1048

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8785
5	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	135 Min. - 165 Max.	163.8
6	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	Report	18.35
7	Viscosity Index	ASTM D-2270	90 Min.	125
8	Flash Point , COC	ASTM D-92	°C	210 Min.	228
9	Pour Point	ASTM D-97	°C	-3 Max.	-9

REMARK –SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAYE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.