



**LABORATORY TEST REPORT**

PRODUCT NAME: HYDRAULIC OIL 68-S	DATE : 15/12/2024
BATCH NO : SL/24-12/1559	LAB.SR.NO. – 1049

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle test	Visual	....	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8746
4	Colour	ASTM D 1500	....	L2.5 Max.	L2.0
5	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	61.2 Min. - 74.8 Max.	66.62
6	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	Report	10.32
7	Viscosity Index	ASTM D2270	....	90 Min.	141
8	Pour Point	ASTM D97	°c	-3 Min.	-9
9	Flash Point ,COC	ASTM D92	°c	210 Min.	212

REMARK – SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY : SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.