



LABORATORY TEST REPORT

| | |
|--------------------------------|-------------------|
| PRODUCT NAME: SPINDLE OIL EE 2 | DATE : 15/12/2024 |
| BATCH NO: SL/24-12/1569 | LAB SR.NO.- 993 |

| SR.NO | TEST | TEST METHOD | UNIT | SPECIFICATION | BATCH TEST REPORT |
|-------|----------------------------|-------------|-------|---------------------|-------------------|
| 1 | Appearance | Visual | | Clear & Bright | Clear & Bright |
| 2 | Crackle test | Visual | | NIL | Nil |
| 3 | Density @ 29.5°C | ASTM D 1298 | Kg/ml | Report | 0.8119 |
| 4 | Colour | ASTM D 1500 | | L2.5 Max. | L0.0 |
| 5 | Kinematic Viscosity @ 40°C | ASTM D 445 | cSt | 2.0 Min. - 3.0 Max. | 2.45 |
| 6 | Flash Point. PMCC | ASTM D92 | °c | 80 Min. | 108 |
| 7 | Copper Corrosion Test | ASTM D-130 | °c | 1a Min. | 1a pass |

REMARK : SAMPLE PASS

TESTED BY : ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com