

SHIELD LUBRICANTS & SPECIALITIES PVT. LTD.

BLEND AUTHORIZATION NOTE (BAN)

PRODUCT : PREMIUM HYDRAULIC OIL HLP 68				DATE OF ISSUE : 12/12/24			
GRADE/API CLASS : ISO VG 68				BATCH NO. : SL/24-12/1582			
FORMULATION NO. :				FLUSHING REQUIRED			
QNTY (LTR) :	1050	QNTY (KG) :	876.54	BLENDER NO.	BK :	TEMP. :	

Special Instruction : WATER WHITE MATERIAL

Raw Materials	Specific Gravity @ 29.5°C	% by wt.	wt. in. kgs.	Vol. in ltr.	(To be advise by Lab)	Source	Actual Qnty. In Kgs.	Actual Qnty. In Vol.	
N 150 GR II	0.8336	92.50	810.80	972.65					
N 500 GR II	0.85	0.00	0.00	0.00					
HITEC 523		0.00	0.00						
KUSA PPD SVX		0.00	0.00						
VM 7077	0.8366	7.50	65.74						
TOTAL		100.00	876.54						
Correction :	1st	2nd				3rd			
Reason :	Viscosity								
Advised for :									

Flushing oil Used :		Total Qnty in Kgs. :	
Qnty :		Total Qnty in Ltrs. :	
BAN ISSUED BY :		Specific Gravity @ 29.5°C	
		Blending Officer Sign :	

FILLING DETAILS:											
PACK SIZE	210	26	25	15	10	7.5	5	4	3	1	0.18
CONTAINS	1	1	1	1	1	1	4	4	4	20	60
ORDER	5										
TOTAL LTR	1050	0	0	0	0	0	0	0	0	0	0
COUPON RS.											
UNIT MRP RS.											
BOX MRP RS.							0	0	0	0	0
USP RS.			0.00	0	0	0	0	0	0	##	0.00
PKG INSTRUCTION	OLD HDPE BRL										
SPECIAL Instruction											

BELOW PART FOR PLANT USE

ACTUAL FILLING											
TOTAL LTR											
TOTAL KG											
GROSS WT											

Manager Plant

Note : BAN (2+1) COPY. 1st copy for Lab, 2nd for SLSPL, 3rd for Production/EDP