



**LABORATORY TEST REPORT**

PRODUCT NAME: SHIELD FLEET POWER MAX 15W40 API CF-4	DATE : 07/01/2025
BATCH NO : SL/25-01/1695	LAB.SR.NO. – 1161

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	....	Nil	Nil
3	Colour	ASTM D-1500	....	L4.0 Max.	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8597
5	Kinematic Viscosity @ 100°C	ASTM D-445	cST	14.00 Min. - 15.50 Max.	14.50
6	Kinematic Viscosity @ 40°C	ASTM D-445	cST	Report	102.7
7	Viscosity Index	ASTM D-2270	....	130 Min.	145
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	Report	10.08
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	228
10	Pour Point	ASTM D-97	°C	- 24 Max.	-27

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.