



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT. NAME.: PERFORMANCE FORMULA 4T 10W30 API SM	DATE : 07/11/2024
BATCH. NO. : SL/24-11/1259	LAB.SR.NO. : 876

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8450
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	10.50 Min. - 12.50 Max.	10.94
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	66.26
7	Viscosity Index	ASTM D-2270	130 Min.	156
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	6.20 Min.	6.21
9	Flash Point,COC	ASTM D-92	°C	190 Min.	212
10	Pour Point	ASTM D-97	°C	- 24 Max.	-27

REMARK – SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.