



**Shield Lubricants & Specialities Pvt. Ltd.**

**LABORATORY TEST REPORT**

PRODUCT. NAME.: FLEET POWER EDGE 10W30 API CK-4	DATE : 29/01/2025
BATCH. NO. : SL/25-01/1879	LAB.SR.NO. : 1263

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	....	Nil	Nil
3	Colour	ASTM D-1500	....	L4.0 Max.	L2.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8531
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	10.00 Min. - 12.50 Max.	12.42
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	80.19
7	Viscosity Index	ASTM D-2270	....	130 Min.	152
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.5 Min.	9.66
9	Flash Point, COC	ASTM D-92	°C	190 Min.	208
10	Pour Point	ASTM D-97	°C	-27 Max.	-30

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,  
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.  
L—022-27582828, Website-www.shieldlubricants.com