



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME : PERFORMANCE DRIVE 4T API SN 20W40	DATE : 07/04/2025
BATCH NO : SL/25-04/038	LAB.SR.NO. – 1508

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Reported	0.8628
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.29
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Reported	118.8
7	Viscosity Index	ASTM D-2270	110 Min.	120
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.3 Min.	7.66
9	Pour Point	ASTM D97	°C	-33 Max.	-33
10	Flash Point, COC	ASTM D92	°C	210 Min.	228

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.