



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: SHIELD FLEET POWER MULTI 20W40 API CF-4	DATE : 15/04/2025
BATCH NO : SL/25-04/040	LAB.SR.NO. – 050

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	Red	Red
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8566
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	15.04
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	104.0
7	Viscosity Index	ASTM D-2270	110 Min.	151
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.50 Min.	10.09
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	214
10	Pour Point	ASTM D-97	°C	- 24 Max.	-27

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHIYAJE