



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME : FLEET POWER ULTRA 40 API CF	DATE : 08/05/2025
BATCH NO : SL/25-05/231	LAB.SR.NO. – 149

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	Red	Red
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8898
5	Kinematic Viscosity @ 100°C	ASTM D-445	cST	15.00 Min. - 16.30 Max.	15.29
6	Kinematic Viscosity @ 40°C	ASTM D-445	cST	Report	106.2
7	Viscosity Index	ASTM D-2270	95 Min.	151
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	8.0 Min.	8.56
9	Pour Point	ASTM D97	°C	-9 Max.	-9
10	Flash Point, COC	ASTM D92	°C	220 Min.	232

REMARK –SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com