



LABORATORY TEST REPORT

PRODUCT NAME : FLEET POWER SUPREME 15W40 API CK-4	DATE : 10/05/2025
BATCH. NO. : SL/24-05/237	LAB.SR.NO : 150

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.5	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8569
5	Kinematic Viscosity @100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.20
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	98.66
7	Viscosity Index	ASTM D-2270	130 Min.	147
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.50 Min.	9.76
9	Flash Point, COC	ASTM D-92	°C	210 Min.	228
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE