



LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER MAX 15W40 API CF-4	DATE : 20/05/2025
BATCH NO : SL/25-05/326	LAB.SR.NO. – 195

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8518
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.29
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	94.11
7	Viscosity Index	ASTM D-2270	130 Min.	156
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.5 Min.	9.64
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	214
10	Pour Point	ASTM D-97	°C	- 24 Max.	-30

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.