



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME : GEAR LUBE EP 150	DATE : 05/03/2025
BATCH NO. : SL/25-03/2096	LAB.SR.NO. -1415

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8838
5	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	135 Min. - 165 Max.	150.8
6	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	Report	15.10
7	Viscosity Index	ASTM D-2270	90 Min.	126
8	Flash Point , COC	ASTM D-92	°C	210 Min.	218
9	Pour Point	ASTM D-97	°C	-3 Max.	-12

REMARK –SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAYE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.