



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER SYNERGY 20W40 API CH4	DATE : 27/03/2025
BATCH NO : SL/25-03/2246	LAB.SR.NO. – 1513

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L2.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8627
5	Kinematic Viscosity @ 100°C	ASTM D-445	cST	14.00 Min. - 15.50 Max.	14.52
6	Kinematic Viscosity @ 40°C	ASTM D-445	cST	Report	101.3
7	Viscosity Index	ASTM D-2270	130 Min.	148
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	Report	10.07
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	216
10	Pour Point	ASTM D-97	°C	- 24 Max.	-27

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.