



**LABORATORY TEST REPORT**

PRODUCT NAME: PREMIUM HYDRAULIC OIL HLP 32	DATE : 27/04/2025
BATCH NO: SL/25-04/175	LAB.SR.NO. – 109

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	-	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	-	NIL	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8421
4	Colour	ASTM D 1500	-	L2.5 Max.	L0.0
5	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	Report	5.36
6	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	28.8 – 35.2	30.56
7	Viscosity Index	ASTM D 2270	-	90 Min.	108
8	Flash Point ,COC	ASTM D92	°C	180 Min.	218
9	Pour Point	ASTM D97	°C	-3 Min.	-18

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.