



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER MULTI 20W40 API CF-4	DATE : 29/05/2025
BATCH NO : SL/25-05/366	LAB.SR.NO. – 241

SR. NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	Red	Red
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8498
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.91
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	97.68
7	Viscosity Index	ASTM D-2270	130 Min.	159
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	9.5 Min.	9.63
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	214
10	Pour Point	ASTM D-97	°C	- 24 Max.	-30

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.