



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: RUSTIC DW 32	DATE : 28/06/2025
BATCH NO: SL/25-06/580	LAB.SR.NO. -367

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	-	Clear & Bright	Clear & Bright
2	Density @ 29.5°C	ASTM D 1298	Kg/ml	Reported	0.7896
3	Colour	ASTM D 1500	L3.0 Max.	L1.5
4	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	1.3 Min. - 3.5 Max.	1.42
5	Flash Point PMCC.	ASTM D-91	°C	40 Min.	56
6	Water Displacement Test	Pass
7	Cu Corrosion Test@100°C	ASTM D130	°C	1A Pass	1A pass
8	Salt Spray Test	ASTM B117-2003	Hrs.	20 Min. - 30 Max.	24

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L-022-27582828, Website-www.shieldlubricants.com