



Shield Lubricants & Specialities Pvt. Ltd.

Regd. Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
+91 22-27582828, Website-www.shieldlubricants.com

CERTIFICATE OF ANALYSIS

PRODUCT NAME : SHIELD WARRIOR HLP 46 ISO VG 46	DATE : 23/08/2025
BATCH NO. : SL/25-08/960	LAB.SR.NO.: 619

Sr. No.	Tests	Units	Method	Minimum	Maximum	Test Results
1	Appearance	None	Visual	Clear & Bright		Clear & Bright
2	Crackle Test	None	Visual	Negative		Negative
3	Density @ 29.5°C	Kg/ml	ASTM D1298	Report		0.8512
4	Colour	None	ASTM D1500		L2.5	L0.5
5	Kinematic, Viscosity @ 100°C	cSt	ASTM D445	Report		6.85
6	Kinematic, Viscosity @ 40°C	cSt	ASTM D445	41.4	50.60	43.42
7	Viscosity Index	None	ASTM D2270	90		114
8	Total Acid Number, TAN	mg KOH/g	ASTM D974		1	0.95
9	Flash Point, COC	°C	ASTM D92	180		220
10	Pour Point	°C	ASTM D97		-15	-24
11	Demulsibility @ 54°C±1°C	minutes	ASTM D1401		0 – 37-3 (30)	40-0-0(20)
12	Foam Test	ml	ASTM D892			
	Seq - I				150/0	20/0
	Seq - II				75/0	10/0
	Seq - III				150/0	20/0

Checked By: ANIL JARHAD

Approved By: Sandip Bhayaje

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.