



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME.:SHIELD MFL 32 ISO VG 32	DATE : 21/09/2025
BATCH. NO.: SL/25-09/1170	LAB.SR.NO.- 752

SR.NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle test	Visual	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8702
4	Colour	ASTM D 1500	...	L2.5 Max.	L1.5
5	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	28.80 Min. - 35.20 Max.	31.30
6	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	Report	5.34
7	Viscosity Index	ASTM D2270	90 Min.	103
8	Flash Point, COC	ASTM D92	°C	180 Min.	220
9	Pour Point	ASTM D-97	°C	-3 Max.	-9

REMARK : SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com