



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

| | |
|--|-------------------|
| PRODUCT NAME. : PRO GEAR EP 140 API GL-4 | DATE : 22/09/2025 |
| BATCH NO. : SL/25-09/1175 | LAB.SR.NO. : 754 |

| SR. NO. | TEST | TEST METHOD | UNIT | SPECIFICATION | BATCH TEST REPORT |
|---------|-----------------------------|-------------|--------------|-------------------|-------------------|
| 1 | Appearance | Visual | | Clear & Bright | Clear & Bright |
| 2 | Crackle Test | Visual | | Nil | Nil |
| 3 | Colour | ASTM D-1500 | | L4.0 Max. | L2.5 |
| 4 | Density @29.5°C | ASTM D-1298 | Kg/ml | Report | 0.8964 |
| 5 | Kinematic Viscosity @ 100°C | ASTM D-445 | cSt | 27 Min. - 31 Max. | 30.10 |
| 6 | Kinematic Viscosity @ 40°C | ASTM D-445 | cSt | Report | 503.5 |
| 7 | Viscosity Index | ASTM D-2270 | | Report | 87 |
| 8 | TAN, mg of KOH/gm | ASTM D-974 | mg of KOH/gm | Report | 0.72 |
| 9 | Flash Point , COC | ASTM D-92 | °C | 220 Min. | 248 |
| 10 | Pour Point | ASTM D-97 | °C | -9 Max. | -12 |

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.