



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME. : PRO GEAR EP 140 API GL-4	DATE : 08/10/2025
BATCH NO. : SL/25-10/1291	LAB.SR.NO. : 837

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L2.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8915
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	27 Min. - 31 Max.	28.82
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	472.0
7	Viscosity Index	ASTM D-2270	Report	86
8	TAN, mg of KOH/gm	ASTM D-974	mg of KOH/gm	Report	0.48
9	Flash Point , COC	ASTM D-92	°C	220 Min.	228
10	Pour Point	ASTM D-97	°C	-9 Max.	-15

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.