



**Shield Lubricants & Specialities Pvt. Ltd.**

## LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER MAX 15W40 API CF-4	DATE : 10/10/2025
BATCH NO: SL/25-10/1330	LAB.SR.NO. – 847

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle test	Visual	....	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8553
4	Colour	ASTM D 1500		L4.0 Max.	L1.5
5	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14 Min. - 15.50 Max.	14.85
6	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	Report	106.3
7	Viscosity Index	ASTM D 2270	....	130 Min.	145
8	Total Base Number	ASTM D2896	MgKOH/g	Report	7.08
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	232
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK: SAMPLE PASS

TESTED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,  
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.  
L—022-27582828, Website-www.shieldlubricants.com