



Shield Lubricants & Specialities Pvt. Ltd.

CERTIFICATE OF ANALYSIS

PRODUCT NAME: FLEET POWER TURBO 15W-40 API CH4	DATE : 09/11/2025
BATCH NO. : SL/25-11/1467	LAB.SR.NO.: 968

Sr. No.	Tests	Units	Method	Minimum	Maximum	Test Results
1	Appearance	Visual	Clear & Bright		Clear & Bright
2	Crackle Test	Visual	Nil		Nil
3	Density @ 29.5°C	Kg/ml	ASTM D1298	Report		0.8619
4	Colour	ASTM D1500		L4.0	L2.0
5	Kinematic,Viscosity @ 40°C	cSt	ASTM D445	Report		122.9
6	Kinematic,Viscosity @ 100°C	cSt	ASTM D445	14	15.5	15.38
7	Viscosity Index	ASTM D2270	130		130
8	Total Base Number, TBN	mg KOH/g	ASTM D2896	8		8.10
9	Flash Point, COC	°C	ASTM D92	210		228
10	Pour Point	°C	ASTM D97		-24	-27

REMARK: SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com