



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER MAX 15W40 API CF-4	DATE : 17/12/2025
BATCH NO: SL/25-12/1817	LAB.SR.NO. – 1157

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle test	Visual	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8443
4	Colour	ASTM D 1500		L4.0 Max.	L1.5
5	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14 Min. - 15.50 Max.	14.47
6	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	Report	92.23
7	Viscosity Index	ASTM D 2270	130 Min.	163
8	Total Base Number	ASTM D2896	MgKOH/g	9.5 Min.	10.90
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	212
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK: SAMPLE PASS

TESTED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com