



LABORATORY TEST REPORT

PRODUCT NAME :SHIELD PERFORMANCE DRIVE 4T 20W40 API SN	DATE : 19/12/2025
BATCH NO : SL/25-12/1840	LAB.SR.NO. – 1168

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8687
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.16
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	125.5
7	Viscosity Index	ASTM D-2270	110 Min.	112
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.3 Min.	8.34
9	Pour Point	ASTM D97	°C	-24 Max.	-30
10	Flash Point, COC	ASTM D92	°C	210 Min.	232

REMARK: SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.