



LABORATORY TEST REPORT

PRODUCT NAME : PROTECTOR 4T SAE 20W40 API SL	DATE : 06/01/2026
BATCH NO : SL/26-01/1933	LAB.SR.NO. – 1249

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L1.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8479
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.44
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	96.32
7	Viscosity Index	ASTM D-2270	110 Min.	155
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	4.5 Min.	4.75
9	Pour Point	ASTM D97	°C	-24 Max.	-27
10	Flash Point, COC	ASTM D92	°C	210 Min.	218

REMARK – SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.