

LABORATORY TEST REPORT

PRODUCT NAME :SHIELD MOTOR DYNA SYNTH 5W40 API SN	DATE :08/01/2026
BATCH. NO : SL/26-01/1956	LAB.SR.NO : 1256

Sr. No.	Tests	Unit	Method	Minimum	Maximum	Batch Test Result
1.	Appearance	----	Visual	Clear & Bright		Clear & Bright
2.	Crackle Test	----	Visual	Nil		Nil
3.	Density @ 29.5°C	Kg/ml	ASTM D1298	Report		0.8450
4.	Colour	----	ASTM D 1500	----	L4.0 Max.	L1.5
5.	Kinematic Viscosity @ 40°C	cSt	ASTM D 445	Report		93.20
6.	Kinematic Viscosity @ 100°C	cSt	ASTM D 445	13.80	15.50	14.12
7.	Viscosity Index	----	ASTM D 2270	150	----	156
8.	Flash Point (COC)	°C	ASTM D 92	190	----	224
9.	Pour Point	°C	ASTM D 97		-33	-36
10.	TBN, mg KOH/g	mg KOH/gm	ASTM D2896	7.3		7.57

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.