



LABORATORY TEST REPORT

PRODUCT NAME : SHIELD FLEET POWER PREMIUM 15W40 CI-4+	DATE : 19/01/2026
BATCH. NO. : SL/26-01/1996	LAB.SR.NO : 1308

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L3.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8661
5	Kinematic Viscosity @100°C	ASTM D-445	cST	14.00 Min. - 15.50 Max.	15.45
6	Kinematic Viscosity @ 40°C	ASTM D-445	cST	Report	123.8
7	Viscosity Index	ASTM D-2270	130 Min.	130
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	Report	10.51
9	Flash Point, COC	ASTM D-92	°C	210 Min.	238
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE