



**Shield Lubricants & Specialities Pvt. Ltd.**

## **LABORATORY TEST REPORT**

PRODUCT NAME : FLEET POWER PLATINUM 15W40 CI-4+	DATE : 19/02/2026
BATCH. NO. : SL/26-02/2283	LAB.SR.NO : 1455

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	....	Nil	Nil
3	Colour	ASTM D-1500	....	L4.0 Max.	L3.0
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8692
5	Kinematic Viscosity @100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.98
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	118.5
7	Viscosity Index	ASTM D-2270	....	130 Min.	130
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	10 Min.	10.22
9	Flash Point, COC	ASTM D-92	°C	210 Min.	230
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK – SAMPLE PASS

PREPARED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,  
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.  
L—022-27582828, Website-www.shieldlubricants.com