



LABORATORY TEST REPORT

PRODUCT NAME :SHIELD PERFORMANCE FORMULA 4T 20W40 API SM	DATE : 23/02/2026
BATCH NO : SL/26-02/2299	LAB.SR.NO. – 1475

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	Red	Red
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8790
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.95
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	137.0
7	Viscosity Index	ASTM D-2270	110 Min.	110
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	6.00 Min.	6.81
9	Pour Point	ASTM D97	°C	-24 Max.	-27
10	Flash Point, COC	ASTM D92	°C	210 Min.	228

REMARK – SAMPLE PASS

TESTED BY: ANIL JARHAD

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.