



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME: FLEET POWER MULTI 20W40 API CF-4	DATE : 14/03/2026
BATCH NO: SL/26-03/2424	LAB.SR.NO. – 1568

SR.NO	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle test	Visual	Nil	Nil
3	Density @ 29.5°C	ASTM D 1298	Kg/ml	Report	0.8461
4	Colour	ASTM D 1500		Red	Red
5	Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14 Min. - 15.50 Max.	14.57
6	Kinematic Viscosity @ 40°C	ASTM D 445	cSt	Report	94.38
7	Viscosity Index	ASTM D 2270	130 Min.	160
8	Total Base Number	ASTM D2896	MgKOH/g	9.5 Min.	9.98
9	Flash Point ,COC	ASTM D-92	°C	210 Min.	220
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK: SAMPLE PASS

TESTED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com