



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME : FLEET POWER PREMIUM 15W40 CI-4+	DATE : 11/03/2026
BATCH. NO. : SL/26-03/2462	LAB.SR.NO : 1554

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L2.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8438
5	Kinematic Viscosity @100°C	ASTM D-445	cSt	14.00 Min. - 15.50 Max.	14.80
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	116.2
7	Viscosity Index	ASTM D-2270	130 Min.	130
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	10 Min.	10.20
9	Flash Point, COC	ASTM D-92	°C	210 Min.	234
10	Pour Point	ASTM D-97	°C	-24 Max.	-27

REMARK – SAMPLE PASS

PREPARED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com