



LABORATORY TEST REPORT

PRODUCT NAME : MOTOR PREMIUM 5W30 API SN-CF	DATE : 14/03/2026
BATCH NO. : SL/26-03/2468	LAB.SR.NO. : 1573

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8442
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	10.50 Min. - 12.50 Max.	10.96
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	67.01
7	Viscosity Index	ASTM D-2270	140 Min.	155
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.3 Min.	7.49
9	Flash Point , COC	ASTM D-92	°C	190 Min.	220
10	Pour Point	ASTM D-97	°C	-33 Max.	-33

REMARK – SAMPLE PASS

PREPARED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.