



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT.NAME. :SHIELD PERFORMANCE TECH 4T 15W50 API SM	DATE : 17/03/2026
BATCH. NO. : SL/26-03/2494	LAB.SR.NO. – 1584

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright.
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L4.0 Max	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8680
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	17.50 Min. - 20.50 Max.	18.48
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	177.1
7	Viscosity Index	ASTM D-2270	120 Min.	116
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.30 Min.	8.43
9	Flash Point , COC	ASTM D-97	°C	210 Min.	236
10	Pour Point	ASTM D-92	°C	-27 Max.	-33

REMARK: SAMPLE PASS

TESTED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com