



**Shield Lubricants & Specialities Pvt. Ltd.**

**LABORATORY TEST REPORT**

PRODUCT.NAME. :SHIELD PERFORMANCE TECH 4T 15W50 API SM	DATE : 23/03/2026
BATCH. NO. : SL/26-03/2509	LAB.SR.NO. – 1609

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	....	Clear & Bright	Clear & Bright.
2	Crackle Test	Visual	....	Nil	Nil
3	Colour	ASTM D-1500	....	L4.0 Max	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8634
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	17.50 Min. - 20.50 Max.	19.65
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	175.5
7	Viscosity Index	ASTM D-2270	....	120 Min.	129
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	7.30 Min.	7.40
9	Flash Point , COC	ASTM D-97	°C	210 Min.	234
10	Pour Point	ASTM D-92	°C	-27 Max.	-30

REMARK: SAMPLE PASS

TESTED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,  
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.  
L—022-27582828, Website-www.shieldlubricants.com