



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT. NAME.: PERFORMANCE FORMULA 4T 10W30 API SN	DATE :11/04/2026
BATCH. NO. : SL/26-04/056	LAB.SR.NO. : 035

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L1.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8
5	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	10.50 Min. - 12.50 Max.	10.68
6	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	Report	70.94
7	Viscosity Index	ASTM D-2270	130 Min.	139
8	TBN, mg of KOH/gm	ASTM D-2896	mg of KOH/gm	6.0 Min.	6.52
9	Flash Point,COC	ASTM D-92	°C	190 Min.	220
10	Pour Point	ASTM D-97	°C	- 30 Max.	-33

REMARK – SAMPLE PASS

PREPARED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE.

Regd.Office: Shelton Sapphire, 8TH Floor, 806-B, Plot No: 18-19, Sector-15,
CBD Belapur, Navi Mumbai-400614, Maharashtra. India.
L—022-27582828, Website-www.shieldlubricants.com