



Shield Lubricants & Specialities Pvt. Ltd.

LABORATORY TEST REPORT

PRODUCT NAME :SHIELD MFL 150 ISO 150	DATE : 02/05/2026
BATCH NO. : SL/26-05/142	LAB.SR.NO. – 101

SR. NO.	TEST	TEST METHOD	UNIT	SPECIFICATION	BATCH TEST REPORT
1	Appearance	Visual	Clear & Bright	Clear & Bright
2	Crackle Test	Visual	Nil	Nil
3	Colour	ASTM D-1500	L3.0 Max.	L2.5
4	Density @29.5°C	ASTM D-1298	Kg/ml	Report	0.8725
5	Kinematic Viscosity @ 40°C	ASTM D-445	cSt	135 Min. - 165 Max.	154.1
6	Kinematic Viscosity @ 100°C	ASTM D-445	cSt	Report	17.17
7	Viscosity Index	ASTM D-2270	90 Min.	121
8	Flash Point , COC	ASTM D-92	°C	210 Min.	228
9	Pour Point	ASTM D-97	°C	-3 Max.	-12

REMARK –SAMPLE PASS

TESTED BY: RAJANI MORE

APPROVED BY: SANDIP BHAYAJE

DISCLAIMER: THIS IS A COMPUTER-GENERATED REPORT AND DOES NOT REQUIRE A PHYSICAL SIGNATURE